## Genuine Eminence LEGEND 875 - LEAD GUITAR SPEAKER

- THE EMINENCE LEGEND 875 IS AN AFFORDABLE ALL PURPOSE 4 OHM 75 WATT SPEAKER
- GREAT FOR PRACTICE AMPS, PORTABLE AMPS AND AS A GREAT REPLACEMENT IN SOME OF YOUR VINTAGE FAVORITES
- WORKS NICELY IN A 4 x 8 CABINET FOR ACOUSTIC APPLICATIONS

## YOU'LL LOVE THE TONE FROM THE EMINENCE LEGEND 875 8" GUITAR SPEAKER!





**SOLD OUT** Item Price: \$49.99

## SPEAKER MODEL

## **I FGFND 875**

| SPEAKER MODEL             | LEGEND 0/3                    |
|---------------------------|-------------------------------|
| Spec                      | ifications                    |
| Nominal Basket Diameter   | 8" / 203.2mm                  |
| Impedance                 | 4 ohms                        |
| RMS Power Rating          | 75 Watts                      |
| Usable Frequency Response | 78Hz - 6kHz                   |
| Voice Coil Diameter       | 1.5" / 38.1mm                 |
| Sensitivity (1W/1m)       | 95dB                          |
| Magnet Weight             | 16 oz.                        |
| Shipping Weight           | 4.8lbs. / 2.2kg.              |
| Mounting                  | g Information                 |
| Overall Diameter          | 8.24" / 209.2                 |
| Bolt Circle Diameter      | 7.75" / 196.9mm               |
| Baffle Cutout Diameter    | 7.13" / 181mm                 |
| No. Of Mounting Holes     | 8                             |
| Mounting Hole Diameter    | 0.218" / 5.5mm                |
| Overall Depth             | 3.58" / 91mm                  |
| Ma                        | iterials                      |
| Basket                    | Pressed Steel                 |
| Voice Coil                | Polyamide-Imide Coated Copper |
| Dust Cap                  | Solid Composition Paper       |
| Cone                      | Paper                         |
| Surround                  | Paper Cone Edge               |
| Magnet                    | Ferrite                       |
| Thiele-Sm                 | all Parameters                |

| Resonant Frequency (fs)            | 88 Hz                   |
|------------------------------------|-------------------------|
| Impedance (Re)                     | 3.88 ohms               |
| Coil Inductance (Le)               | 0.34mH                  |
| Electromagnetic Q (Qes)            | .70                     |
| Mechanical Q (Qms)                 | 4.27                    |
| Total Q (Qts)                      | .60                     |
| Compliance Equivalent Vol. (Vas)   | 18.7 Liters / .66cu.ft. |
| Voice Coil Overhang (Xmax)         | 1.3mm                   |
| Surface Area of Cone (Sd)          | .02141m2                |
| BL Product (BL)                    | 5.9 T-M                 |
| Displacement Volume (Vd)           | 27 cc                   |
| Diaphragm Mass Inc. Airload (Mms)  | 11 grams                |
| Mechanical Compliance (Cms)        | .29mm/N                 |
| Mechanical Resistance (RMS)        | 1.47N*sec/M             |
| Efficiency Bandwidth Product (EBP) | 126                     |
| Impedance at Resonance (Zmax)      | 28 ohms                 |
| 110                                |                         |
| 100                                |                         |
| 90                                 | 7111-7-7-1711           |
| 80                                 |                         |
| 60                                 |                         |
| 50                                 |                         |
| 20Hz 100 50                        | 0 1k 5k 20k             |



US Speaker, LLC