

MOSFET – N-Channel, Logic Level, **POWERTRENCH**[®] 60 V, 4 A, 60 mΩ

FDC5661N-F085

Features

- $R_{DS(on)} = 47\text{ m}\Omega$ at $V_{GS} = 10\text{ V}$, $I_D = 4.3\text{ A}$
- $R_{DS(on)} = 60\text{ m}\Omega$ at $V_{GS} = 4.5\text{ V}$, $I_D = 4\text{ A}$
- Typ $Q_g(TOT) = 14.5\text{ nC}$ at $V_{GS} = 10\text{ V}$
- Low Miller Charge
- UIS Capability
- AEC-Q101 Qualified and PPAP Capable
- This Device is Pb-Free, Halogen Free/BFR Free and is RoHS Compliant

Applications

- DC/DC Converter
- Motor Drives

MOSFET MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| Rating | Symbol | Value | Unit |
|--|-----------------|-------------|--------------------|
| Drain to Source Voltage | V_{DSS} | 60 | V |
| Gate to Source Voltage | V_{GS} | ± 20 | V |
| Drain Current Continuous ($V_{GS} = 10\text{ V}$) | I_D | 4.3 | A |
| Pulsed | | 20 | |
| Single Pulse Avalanche Energy (Note 1) | E_{AS} | 81 | mJ |
| Power Dissipation | P_D | 1.6 | W |
| Operating and Storage Temperature | T_J, T_{STG} | -55 to +150 | $^\circ\text{C}$ |
| Thermal Resistance Junction to Case | $R_{\theta JC}$ | 30 | $^\circ\text{C/W}$ |
| Thermal Resistance Junction to Ambient TO-263, 1in ² Copper Pad Area | $R_{\theta JA}$ | 78 | $^\circ\text{C/W}$ |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. E_{AS} of 81 mJ is 100% test at $L = 14\text{ mH}$, $I_{AS} = 3.4\text{ A}$, Starting $T_J = 25^\circ\text{C}$




ON Semiconductor[®]

www.onsemi.com



TSOT23-6
CASE 419BL


MARKING DIAGRAM



XXX = Specific Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

FDC5661N-F085

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|-----------|--------|----------------|-----|-----|-----|------|
|-----------|--------|----------------|-----|-----|-----|------|

OFF CHARACTERISTICS

| | | | | | | |
|-----------------------------------|------------|---|---------------------------|---|-----------|---------------|
| Drain to Source Breakdown Voltage | B_{VDSS} | $I_D = 250 \mu\text{A}, V_{GS} = 0 \text{ V}$ | 60 | - | - | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = 48 \text{ V}, V_{GS} = 0 \text{ V}$ | - | - | 1 | μA |
| | | | $T_A = 150^\circ\text{C}$ | - | - | |
| Gate to Source Leakage Current | I_{GSS} | $V_{GS} = \pm 20 \text{ V}$ | - | - | ± 100 | nA |

ON CHARACTERISTICS

| | | | | | | |
|----------------------------------|--------------|--|---------------------------|-----|----|------------------|
| Gate to Source Threshold Voltage | $V_{GS(th)}$ | $V_{GS} = V_{DS}, I_D = 250 \mu\text{A}$ | 1 | 2.0 | 3 | V |
| Drain to Source On-Resistance | $R_{DS(on)}$ | $V_{GS} = 10 \text{ V}, I_D = 4.3 \text{ A}$ | - | 38 | 47 | $\text{m}\Omega$ |
| | | $V_{GS} = 4.5 \text{ V}, I_D = 4 \text{ A}$ | - | 46 | 60 | |
| | | $V_{GS} = 10 \text{ V}, I_D = 4.3 \text{ A}$ | $T_J = 150^\circ\text{C}$ | - | 69 | |

DYNAMIC CHARACTERISTICS

| | | | | | | |
|-------------------------------|--------------|---|---|------|----|----------|
| Input Capacitance | C_{iss} | $V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V},$ $f = 1 \text{ MHz}$ | - | 763 | - | pF |
| Output Capacitance | C_{oss} | | - | 68 | - | pF |
| Reverse Transfer Capacitance | C_{rss} | | - | 36 | - | pF |
| Gate Resistance | R_G | $f = 1 \text{ MHz}$ | - | 2.6 | - | Ω |
| Total Gate Charge at 10 V | $Q_{g(TOT)}$ | $V_{GS} = 0 \text{ to } 10 \text{ V}, V_{DD} = 30 \text{ V}, I_D = 4.3 \text{ A}$ | - | 14.5 | 19 | nC |
| Gate to Source Gate Charge | Q_{gs} | $V_{DD} = 30 \text{ V}, I_D = 4.3 \text{ A}$ | - | 2.4 | - | nC |
| Gate to Drain "Miller" Charge | Q_{gd} | | - | 2.9 | - | nC |

SWITCHING CHARACTERISTICS

| | | | | | | |
|---------------------|--------------|--|---|------|------|----|
| Turn-On Time | t_{on} | $V_{GS} = 10 \text{ V}, V_{DD} = 30 \text{ V},$ $I_D = 4.3 \text{ A}, R_{GS} = 6 \Omega,$ | - | - | 17.6 | ns |
| Turn-On Delay Time | $t_{d(on)}$ | | - | 7.2 | - | ns |
| Rise Time | t_r | | - | 1.6 | - | ns |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 19.3 | - | ns |
| Fall Time | t_f | | - | 3.1 | - | ns |
| Turn-Off Time | t_{off} | | - | - | 36 | ns |

DRAIN-SOURCE DIODE CHARACTERISTICS

| | | | | | | |
|-------------------------------|----------|--|---|------|------|----|
| Source to Drain Diode Voltage | V_{SD} | $I_{SD} = 4.3 \text{ A}$ | - | 0.8 | 1.25 | V |
| | | $I_{SD} = 2.1 \text{ A}$ | - | 0.8 | 1.0 | |
| Reverse Recovery Time | t_{rr} | $I_{SD} = 4.3 \text{ A}, dI_{SD}/dt = 100 \text{ A}/\mu\text{s}$ | - | 18.4 | 24 | ns |
| Reverse Recovery Charge | Q_{rr} | | - | 10.0 | 13 | nC |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

FDC5661N-F085

TYPICAL CHARACTERISTICS




Figure 1. Normalized Power Dissipation vs. Ambient Temperature




Figure 2. Maximum Continuous Drain Current vs. Ambient Temperature




Figure 3. Normalized Maximum Transient Thermal Impedance




Figure 4. Peak Current Capability

TYPICAL CHARACTERISTICS (continued)




Figure 5. Forward Bias Safe Operating Area




Figure 6. Transfer Characteristics




Figure 7. Saturation Characteristics




Figure 8. Drain to Source On-Resistance Variation vs. Gate to Source Voltage




Figure 9. Normalized Drain to Source On Resistance vs. Junction Temperature




Figure 10. Normalized Gate Threshold Voltage vs. Junction Temperature

TYPICAL CHARACTERISTICS (continued)




Figure 11. Normalized Drain to Source Breakdown Voltage vs. Junction Temperature




Figure 12. Capacitance vs. Drain to Source Voltage




Figure 13. Gate Charge vs. Gate to Source Voltage

FDC5661N-F085

ORDERING INFORMATION

| Device Marking | Device | Package | Shipping† |
|----------------|---------------|--------------------|--------------------|
| .661N | FDC5661N-F085 | TSOT23-6 (Pb-Free) | 3000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

POWERTRENCH is a registered trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.

MECHANICAL CASE OUTLINE

PACKAGE DIMENSIONS


ON Semiconductor®



1
SCALE 2:1

TSOT23 6-Lead CASE 419BL ISSUE A

DATE 31 AUG 2020




TOP VIEW



FRONT VIEW




DETAIL A



SIDE VIEW

SYMM
⌀



LAND PATTERN
RECOMMENDATION

*FOR ADDITIONAL INFORMATION ON OUR
Pb-FREE STRATEGY AND SOLDERING DETAILS,
PLEASE DOWNLOAD THE ON SEMICONDUCTOR
SOLDERING AND MOUNTING TECHNIQUES
REFERENCE MANUAL, SOLDERRM/D.

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.25MM PER END. DIMENSIONS D AND E1 ARE DETERMINED AT DATUM H.
4. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.

| DIM | MILLIMETERS | | |
|-----|-------------|------|------|
| | MIN. | NOM. | MAX. |
| A | 0.90 | 1.00 | 1.10 |
| A1 | 0.00 | 0.05 | 0.10 |
| A2 | 0.70 | 0.85 | 1.00 |
| A3 | 0.25 BSC | | |
| b | 0.25 | 0.38 | 0.50 |
| c | 0.10 | 0.18 | 0.26 |
| D | 2.80 | 2.95 | 3.10 |
| d | 0.30 REF | | |
| E | 2.50 | 2.75 | 3.00 |
| E1 | 1.30 | 1.50 | 1.70 |
| e | 0.95 BSC | | |
| e1 | 1.90 BSC | | |
| L1 | 0.60 REF | | |
| L2 | 0.20 | 0.40 | 0.60 |
| ⊖ | 0° | -- | 10° |

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|------------------|---------------|--|
| DOCUMENT NUMBER: | 98AON83292G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | TSOT23 6-Lead | PAGE 1 OF 1 |

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[onsemi:](#)

[FDC5661N-F085](#)