

# Material Safety Data Sheet

ITW Consumer - Devcon/Versachem

1 of 5

## QUICK SET 4-MINUTE EPOXY STEEL HARDENER

This product appears in the following stock number(s):  
44209

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Tradename:** QUICK SET 4-MINUTE EPOXY STEEL HARDENER

**General use:** The following health hazard data pertain to the hardener only. When fully cured, the mixed product is non-hazardous

**Chemical family:** Polymercaptan/polyamine mixture

#### MANUFACTURER

ITW Consumer - Devcon/Versachem  
2107 West Blue Heron Blvd.  
Riviera Beach, Florida 33404

#### EMERGENCY INFORMATION

Emergency telephone number  
(CHEMTEL): (800) 255-3924  
(CHEMTEL International): (+01) 813-248-0585  
Other Calls: (561) 845-2425

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Abbr.	Weight%	ACGIH; TLV-TWA	OSHA PEL:	Other Limits
LIMESTONE 1317-65-3	n/e	50-70	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable)	n/e
MERCAPTAN AMINE BLEND MIXTURE	n/e	30-50		n/e	n/e
BENZYL ALCOHOL 100-51-6	BZOH	<10		n/e	10 ppm AIHA
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	n/e	<10	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> total dust	n/e
CRYSTALLINE SILICA 14808-60-7	n/e	0.1-1.0		10(%Q+2) mppcf (respirable)	0.1 mg/m <sup>3</sup> (Canada)
TRADE SECRET (Non-hazardous) MIXTURE	n/e	balance		n/e	n/e

"TLV" means the Threshold Limit Value exposure (eight-hour, time-weighted average, unless otherwise noted) established by the American Conference of Governmental Industrial Hygienists. "STEL" indicates a short-term exposure limit. "PEL" indicates the OSHA Permissible Exposure Limit. "n/e" indicates that no exposure limit has been established. An asterisk (\*) indicates a substance whose identify is a trade secret of our supplier and unknown to us.

### 3. HAZARDOUS IDENTIFICATION

#### Emergency Overview

**Appearance, form, odor:** Viscous Amber liquid with mercaptan odor

**WARNING!** Eye, skin and respiratory irritant. Potential skin sensitizer. Overexposure may cause delayed lung effects.

#### Potential health effects

**Primary Routes of Exposure:** Eye. Skin. Inhalation (breathing)

#### Symptoms of acute overexposure

**Skin:** May cause severe skin irritation. Potential sensitizer.

**Eyes:** Causes severe irritation with possible damage and even blindness

## ITW Consumer - Devcon/Versachem

**Inhalation:** Considered slightly toxic. May cause mild respiratory irritation. Overexposure to fumes or vapors may cause delayed lung injury and chemical pneumonia.

**Ingestion:** Slightly toxic. May cause gastric distress (nausea, vomiting, diarrhea).

**Effects of Chronic Exposure:** Overexposure may cause delayed lung injury and chemical pneumonia. Prolonged or repeated skin contact may cause sensitization, with itching, swelling or rashes on later exposure.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
BENZYL ALCOHOL 100-51-6	<10	male rat-no evidence; female rat-no evidence; male mice- no evidence; female mice-no evidence		
CRYSTALLINE SILICA 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1 Monograph 68, 1997 (inhalation of quartz)

### Medical Conditions Recognized as Being Aggravated by Exposure:

Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

## 4. FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.

**Inhalation:** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person

## 5. FIRE FIGHTING MEASURES

**Recommended Extinguishing Media:** Water, Carbon dioxide, Dry chemical, foam

**Flash point:** >200°F (93.3°C)

**Method:** PMCC

**Lower Explosive**

**Upper Explosive**

**Limit:** n/d

**Limit:** n/d

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact. Use water spray to cool exposed containers.

### Unusual Fire/Explosion Hazards:

Toxic smoke or vapors may form during combustion.

### Hazardous Products of Combustion:

Oxides of carbon, Oxides of sulfur, Oxides of nitrogen

## 6. ACCIDENTAL RELEASE MEASURES

**Spill Control:** Avoid personal contact. Eliminate ignition sources. Ventilate area.

**Containment:** Dike, contain and absorb with clay, sand or other suitable material

**Cleanup:** For large spills, pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Flush area with water.

**Special procedures:** Prevent spill from entering drainage/sewer systems, waterways and surface water.

## 7. HANDLING AND STORAGE

**Handling precautions:** Avoid contact with the skin and the eyes. Wash thoroughly with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing and protective gear before reuse. Discard contaminated leather articles. Handle mixed resin and hardener in accordance with the potential hazard of the curing agent used. Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

**Storage:** Store in a cool, dry area. Store away from heat.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering controls:

#### **Ventilation:**

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Other engineering controls:** Have emergency shower and eye wash available.

### Personal protective equipment

**Eye and face protection:** Safety glasses with side shields or splash-proof goggles are recommended

**Skin protection:** Chemical-resistant gloves (Neoprene, nitrile) and other gear as required to prevent skin contact.

**Respiratory protection:** With good ventilation, none required. In poorly ventilated areas use NIOSH-approved organic vapor cartridge respirator for uncured resin, dust/particle respirators during grinding/sanding operations for cured resin, or fresh airline respirator as exposure levels dictate (see OSHA CFR29 1910.134).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Specific Gravity:** 1.13

**Boiling Point:** n/d

**Melting point:** n/d

**Vapor Density (Air=1):** n/d

**Vapor Pressure:** <1 @ 70°F

**Evaporation Rate:** n/d

**VOC:** 0

**Solubility in water:** Negligible

**pH (5% solution or slurry in water):** 9.5

## 10. STABILITY AND REACTIVITY

This material is chemically stable. Hazardous polymerization will not occur.

**Conditions to Avoid:** Open flame and extreme heat.

**Incompatibilities:** Strong oxidizers

**Hazardous Products of Combustion:** Oxides of carbon, Oxides of sulfur, Oxides of nitrogen

**Conditions under which hazardous polymerization may occur:** When this hardener is mixed with an epoxy resin, heat is generated; be careful when mixing more than an ounce or so.

## 11. TOXICOLOGICAL INFORMATION

**Eye Contact:** No data available.

**Subchronic effects:** No data available.

**Carcinogenicity, tertogenicity and mutagenicity:** No data available.

**Other chronic effects:** Not determined.

**Toxicological information on hazardous chemical constituents of this product:**

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 4hr (rat)
LIMESTONE 1317-65-3	n/d	n/d	n/d
MERCAPTAN AMINE BLEND MIXTURE	n/d	n/d	n/d
BENZYL ALCOHOL 100-51-6	1230 mg/kg	2000 mg/kg	8.8 mg/L/4h
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	n/d	n/d	n/d
CRYSTALLINE SILICA 14808-60-7	n/d	n/d	n/d
TRADE SECRET (Non-hazardous) MIXTURE	n/d	n/d	n/d

'n/d' = not determined

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

**Mobility and persistence:** No data available.

**Environmental fate:** No data available.

## 13. DISPOSAL CONSIDERATIONS

Please see also Section 15, Regulatory Information.

**Recommended Method of Disposal:** If material becomes a waste, it would not be a hazardous waste by RCRA criteria (40CFR 261). Dispose of according to applicable federal, state and local regulations.

**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material.

## 14. TRANSPORT INFORMATION

**Proper shipping name:** Not regulated

**Technical name:** N/A

**Hazard class:** N/A

**UN/ID Number:** N/A

**Packing group:** N/A

**Emergency Response Guide no:** N/A

## 15. REGULATORY INFORMATION

### U.S. Federal Regulations

**TSCA:**

All ingredients of this product are listed or are exempt from listing on the TSCA Inventory.

**The following RCRA code(s) applies to this material if it becomes waste:**

None

**Regulatory status of hazardous chemical constituents of this product:**

Component	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	12B EXPORT NOTIFICATION:
LIMESTONE 1317-65-3	No	No	0.0	Not required
MERCAPTAN AMINE BLEND MIXTURE	No	No	0.0	Not required
BENZYL ALCOHOL 100-51-6	No	No	0.0	Not required
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	No	No	0.0	Not required
CRYSTALLINE SILICA 14808-60-7	No	No	0.0	Not required
TRADE SECRET (Non-hazardous) MIXTURE	No	No	0.0	Not required

\*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substance List.

\*\*Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of Toxic Chemicals, for which release reporting may be required. For specific requirements, consult the appropriate regulations.

**For purposes of SARA Section 312 hazardous materials inventory reporting, the following hazard classes apply to this material:** Immediate health hazard, Delayed health hazard

**California regulations:** For purposes of the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), this product does not contain any chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**Canadian Regulations**

**WHMIS Hazard Class:** D2B TOXIC MATERIALS,  
All components of this product are on the Domestic Substances List

**16. OTHER INFORMATION**

**Hazardous Material Information System (HMIS) rating:**  
Health 3\* Flammability 1 Physical Hazard 0

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Revision Date:** October/22/2008  
**Revision Number:** 3

The information and recommendations in this document are based on the best information available to us at the time of preparation, but we make no other warranty, express or implied, as to its correctness or completeness, or as to the results of reliance on this document.

# Material Safety Data Sheet

ITW Consumer - Devcon/Versachem

1 of 6

## QUICK SET 4-MINUTE EPOXY STEEL RESIN

This product appears in the following stock number(s):  
44209

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Tradename:** QUICK SET 4-MINUTE EPOXY STEEL RESIN

**General use:** This information applies to the resin component of the two-part kit. Handle freshly mixed resin and hardener as recommended for the hardener. After curing, the product is not hazardous

**Chemical family:** Epoxy resin

#### MANUFACTURER

ITW Consumer - Devcon/Versachem  
2107 West Blue Heron Blvd.  
Riviera Beach, Florida 33404

#### EMERGENCY INFORMATION

Emergency telephone number  
(CHEMTEL): (800) 255-3924  
(CHEMTEL International): (+01) 813-248-0585  
Other Calls: (561) 845-2425

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Abbr.	Weight%	ACGIH; TLV-TWA	OSHA PEL:	Other Limits
LIMESTONE 1317-65-3	n/e	30-60	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable)	n/e
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	DGEBPA	30-60		n/e	n/e
IRON 7439-89-6	n/e	<10		n/e	n/e
SILICON DIOXIDE, AMORPHOUS 112945-52-5	n/e	<10	5 mg/m <sup>3</sup> , TWA	6 mg/m <sup>3</sup> TWA	n/e
BENZYL ALCOHOL 100-51-6	BZOH	<5		n/e	10 ppm AIHA
SILICON 7440-21-3	n/e	<5		15 mg/m <sup>3</sup> TWA (total dust); 3 mg/m <sup>3</sup> TWA (respirable)	10 mg/m <sup>3</sup> TWA (total dust); 3 mg/m <sup>3</sup> TWA (respirable) Canada
CRYSTALLINE SILICA 14808-60-7	n/e	0.1-1.0		10(%Q+2) mppcf (respirable)	0.1 mg/m <sup>3</sup> (Canada)
TRADE SECRET (Non-hazardous) MIXTURE	n/e	balance		n/e	n/e

"TLV" means the Threshold Limit Value exposure (eight-hour, time-weighted average, unless otherwise noted) established by the American Conference of Governmental Industrial Hygienists. "STEL" indicates a short-term exposure limit. "PEL" indicates the OSHA Permissible Exposure Limit. "n/e" indicates that no exposure limit has been established. An asterisk (\*) indicates a substance whose identify is a trade secret of our supplier and unknown to us.

### 3. HAZARDOUS IDENTIFICATION

#### Emergency Overview

**Appearance, form, odor:** Black Viscous liquid with little odor

**WARNING!.** Eye and skin irritant. Potential skin sensitizer.

#### Potential health effects

**Primary Routes of Exposure:** Eye and skin contact, ingestion, inhalation

**Symptoms of acute overexposure**

**Skin:** Moderate skin irritant . May cause skin sensitization (itching, redness, rashes, hives, burning, swelling).

**Eyes:** Moderate eye irritant (stinging, burning sensation, tearing, redness, swelling) Overexposure may cause lacrimation, conjunctivitis, corneal damage and may cause permanent injury (i.e. blindness)

**Inhalation:** Irritant. Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.

**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain. May cause gastric distress (nausea, vomiting, diarrhea).

**Effects of Chronic Exposure:** Prolonged or repeated skin contact may cause sensitization, with itching, swelling or rashes on later exposure.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<10			Amorphous Silica, Group 3: Vol. 68: 1997
BENZYL ALCOHOL 100-51-6	<5	male rat-no evidence; female rat-no evidence; male mice- no evidence; female mice-no evidence		
CRYSTALLINE SILICA 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1 Monograph 68, 1997 (inhalation of quartz)

**Medical Conditions Recognized as Being Aggravated by Exposure:**

Preexisting eye and skin disorders( e.g. eczema). Development of preexisting skin or lung allergy symptoms may increase.

**Other:**

See Section 11

**4. FIRST AID MEASURES**

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**Skin Contact:** Immediately remove contaminated clothing and excess contaminant. Flush with water for at least 15 minutes. Wash thoroughly with soap and water. Consult a physician if irritation develops.

**Inhalation:** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person

**5. FIRE FIGHTING MEASURES**

**Recommended Extinguishing Media:** Carbon dioxide, Dry chemical, foam

**Flash point:** >200°F (93.3°C)

**Method:** Estimate

**Lower Explosive  
Limit:** n/d

**Upper Explosive  
Limit:** n/d

**Special Fire-Fighting Procedures:** Material will not burn unless preheated. Do not enter confined space without full bunker gear. Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact. Use water spray to cool exposed containers.

**Unusual Fire/Explosion Hazards:**

Heating above 300°F in the presence of air may cause slow oxidation decomposition and above 500°F may cause polymerization.

**Hazardous Products of Combustion:**

When heated to decomposition it emits fumes of Cl-, carbon monoxide, other fumes and vapors varying in composition and toxicity

**6. ACCIDENTAL RELEASE MEASURES**

**Spill Control:** Avoid personal contact. Eliminate ignition sources. Ventilate area.

**Containment:** Dike, contain and absorb with clay, sand or other suitable material

**Cleanup:** For large spills, pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Flush area with water.

**Special procedures:** Prevent spill from entering drainage/sewer systems, waterways and surface water.

**7. HANDLING AND STORAGE**

**Handling precautions:** Avoid contact with the skin and the eyes. Wash thoroughly with soap and water after using and particularly before eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing and protective gear before reuse. Discard contaminated leather articles. Handle mixed resin and hardener in accordance with the potential hazard of the curing agent used. Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

**Storage:** Store in a cool, dry area. Store away from heat.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering controls:**

**Ventilation:**

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Other engineering controls:** Have emergency shower and eye wash available.

**Personal protective equipment**

**Eye and face protection:** Wear appropriate protective glasses or splash goggles as described by 29CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166

**Skin protection:** Chemical-resistant gloves (i.e. butyl) and other gear as required to prevent skin contact.

**Respiratory protection:** With good ventilation, none required. In poorly ventilated areas use NIOSH-approved organic vapor cartridge respirator for uncured resin, dust/particle respirators during grinding/sanding operations for cured resin, or fresh airline respirator as exposure levels dictate (see OSHA CFR29 1910.134).



## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Specific Gravity:** 1.62

**Boiling Point:** >450°F (232.2°C)

**Melting point:** n/d

**Vapor Density (Air=1):** >1

**Vapor Pressure:** Nil @ 171°F

**Evaporation Rate:** <1 (butyl acetate = 1)

**VOC:** 0

**Solubility in water:** Negligible

**pH (5% solution or slurry in water):** Neutral

## 10. STABILITY AND REACTIVITY

This material is chemically stable. Hazardous polymerization will not occur.

**Conditions to Avoid:** Open flame and extreme heat.

**Incompatibilities:** Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines)

**Hazardous Products of Combustion:** When heated to decomposition it emits fumes of Cl-, carbon monoxide, other fumes and vapors varying in composition and toxicity

**Conditions under which hazardous polymerization may occur:** Heat is generated when resin is mixed with curing agents; Run-away cure reactions may char and decompose the resin, generating unidentified fumes and vapors which may be toxic.

## 11. TOXICOLOGICAL INFORMATION

**Eye Contact:** No data available.

**Subchronic effects:** No data available.

**Carcinogenicity, teratogenicity and mutagenicity:** Both the resin and the diglycidyl ether of bisphenol A (a component of this product) have proved to be inactive when tested by invivo mutagenicity assays. Both have shown activity by invitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat liver cells. Benzyl alcohol may cause reproductive effects.

**Other chronic effects:** 2-year bioassays in mice exposed by the dermal route to EPON 828, DGEBA, or other commercial resins yielded limited evidence of weak carcinogenicity. The authors concluded that the renal tumor evidence with EPON 828 "was of no biological significance" and the resin "is not a systemic carcinogen when applied to the dorsal skin of CF1 mice.". Benzyl alcohol may cause digestive disorders, central nervous system depression and/or lung damage.

### Toxicological information on hazardous chemical constituents of this product:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 4hr (rat)
LIMESTONE 1317-65-3	n/d	n/d	n/d

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 4hr (rat)
BISPHENOL A/EPICHLOROXYDRIN BASED EPOXY RESIN 25068-38-6	11400 mg/kg	n/d	n/d
IRON 7439-89-6	984 mg/kg	n/d	n/d
SILICON DIOXIDE, AMORPHOUS 112945-52-5	n/d	n/d	n/d
BENZYL ALCOHOL 100-51-6	1230 mg/kg	2000 mg/kg	8.8 mg/L/4h
SILICON 7440-21-3	3160 mg/kg	n/d	n/d
CRYSTALLINE SILICA 14808-60-7	n/d	n/d	n/d
TRADE SECRET (Non-hazardous) MIXTURE	n/d	n/d	n/d

'n/d' = not determined

—

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

**Mobility and persistence:** No data available.

**Environmental fate:** No data available.

## 13. DISPOSAL CONSIDERATIONS

Please see also Section 15, Regulatory Information.

**Recommended Method of Disposal:** If resin becomes a waste, it would not be a hazardous waste by RCRA criteria (40CFR 261). Dispose of according to applicable federal, state and local regulations. Incineration is the preferred method of disposal.

**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material.

## 14. TRANSPORT INFORMATION

**Proper shipping name:** Not regulated

**Technical name:** N/A

**Hazard class:** N/A

**UN/ID Number:** N/A

**Packing group:** N/A

**Emergency Response Guide no:** N/A

## 15. REGULATORY INFORMATION

### U.S. Federal Regulations

**TSCA:**

All ingredients of this product are listed or are exempt from listing on the TSCA Inventory.

**The following RCRA code(s) applies to this material if it becomes waste:**

None

**Regulatory status of hazardous chemical constituents of this product:**

**ITW Consumer - Devcon/Versachem**

Component	Extremely Hazardous*	Toxic Chemical**	CERCLA RQ (lbs)	12B EXPORT NOTIFICATION:
LIMESTONE 1317-65-3	No	No	0.0	Not required
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	No	No	0.0	Not required
IRON 7439-89-6	No	No	0.0	Not required
SILICON DIOXIDE, AMORPHOUS 112945-52-5	No	No	0.0	Not required
BENZYL ALCOHOL 100-51-6	No	No	0.0	Not required
SILICON 7440-21-3	No	No	0.0	Not required
CRYSTALLINE SILICA 14808-60-7	No	No	0.0	Not required
TRADE SECRET (Non-hazardous) MIXTURE	No	No	0.0	Not required

\*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substance List.

\*\*Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of Toxic Chemicals, for which release reporting may be required. For specific requirements, consult the appropriate regulations.

**For purposes of SARA Section 312 hazardous materials inventory reporting, the following hazard classes apply to this material:** Immediate health hazard, Delayed health hazard

**California regulations:** For purposes of the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), this product contains a chemical(s) known to cause cancer and birth defects or other reproductive harm.

**Canadian Regulations**

**WHMIS Hazard Class:** D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS,  
All components of this product are on the Domestic Substances List

**16. OTHER INFORMATION**

**Hazardous Material Information System (HMIS) rating:**

Health 2\*    Flammability 1    Physical Hazard 1

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Revision Date:** October/22/2008

**Revision Number:** 4

The information and recommendations in this document are based on the best information available to us at the time of preparation, but we make no other warranty, express or implied, as to its correctness or completeness, or as to the results of reliance on this document.