

# PHOTODIODE PRODUCTS SPECIFICATION

HPDB5-14D-B




Drawn by	Checked by	Approved by



DATE:2009/1/19

REV:E



**HUEY JANN ELECTRONICS INDUSTRY CO., LTD.**


No.27 Line 466 Sec.2,Cannng-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.

TEL:+886-4-26393976 FAX:+886-4-26393125

☰ DEVICES


Part Number	Lens		Source	
	Color	Diffusion	Dice Source	Color
HPDB5-14D-B	Black	Non-Diffused	---	Photodiode

☰ PACKAGE DIMENSIONS:



NOTE:

- 1.All dimensions are in millimeter.
- 2.Lead spacing is measured where the lead emerge from the package.
- 3.protruded resin under flange is 1.5mm max.
- 4.specifications are subject to change without notice.
- 5.Tolerance is  $\pm 0.3$ mm unless otherwise noted.



**HUEY JANN ELECTRONICS INDUSTRY CO., LTD.**

No.27 Line 466 Sec.2, Cangg-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.


TEL:+886-4-26393976 FAX:+886-4-26393125

ABSOLUTE MAXIMUM RATINGS

TA=25°C

PARAMETER	SYMBOL	MAX. RATING	UNIT
Power Dissipation	Pd	50	mW
Reverse Voltage	VR	20	V
Active Area	AA	0.19	mm <sup>2</sup>
Operating Temperature	Topr	-40 ~ +85	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Dip Soldering Temperature (3mm from case Bottom 260 °C for 5 seconds)			

\*Iron soldering in 350°C within 5 seconds will not cause damage to the dice. But be aware of the high temperature will not only make the epoxy soften but also cause the lead moving and the gold wire broken and even open. So before returning to the normal temperature PLEASE AVOID any serious pressure on the top of epoxy and lead.



**HUEY JANN ELECTRONICS INDUSTRY CO., LTD.**

No.27 Line 466 Sec.2,Cannng-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.


TEL:+886-4-26393976 FAX:+886-4-26393125

ELECTRIC-OPTICAL CHARACTERISTICS

TA=25°C

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
View Angle of Half Power	2θ1/2	E=0.5mw/cm <sup>2</sup>		30		deg
Forward Voltage	VF	IF=40mA		1.0	1.5	V
Open Circuit Voltage	Voc	E=0.5mw/cm <sup>2</sup>		390		mV
Light Current	Ip	E=0.5mw/cm <sup>2</sup> VR=10V		10		μA
Dark Current	IR	VR=10V,E=0			30	nA
Peak Wavelength *1	λ p			900		nm
Sensitivity Wavelength	S λ		760		1000	nm
Ries Time	Tr	VR=10V,RI=1KΩ		6		ns
Fall Time	Tf	VR=10V,RI=1KΩ		6		ns

\*1.The dominate wavelength , λ d, is derived from the CIE Chromaticity Diagram and represents the color of the device.



**HUEY JANN ELECTRONICS INDUSTRY CO., LTD.**

No.27 Line 466 Sec.2,Cannng-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.

TEL:+886-4-26393976 FAX:+886-4-26393125

TYPICAL ELECTRICAL OPTICAL CHARACTERISTICS CURVES

Fig.1 Power Dissipation VS. Ambient Temperature




Fig.2 Spectral Sensitivity ( $T_a = 25^\circ\text{C}$ )




Fig.3 Dark Current VS. Ambient Temperature






Fig.4 Reverse Light Current VS.  $E_e$




HUEY JANN ELECTRONICS INDUSTRY CO., LTD.

No.27 Line 466 Sec.2,Canng-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.



TEL:+886-4-26393976 FAX:+886-4-26393125

TYPICAL ELECTRICAL OPTICAL CHARACTERISTICS CURVES

**Fig.5**  
Terminal Capacitance VS. Reverse Voltage  
( $F=1\text{MHz}, V_R=3\text{V}, E_e=0\text{mW/cm}^2$ )



**Fig.6**  
Response Time VS. Load Resistance  
( $V_R=10\text{V}, T_a=25^\circ\text{C}$ )



**HUEY JANN ELECTRONICS INDUSTRY CO., LTD.**

No.27 Line 466 Sec.2,Canng-nan Rd. Wu-chi Town Taichung Shien, Taiwan, R.O.C.

TEL:+886-4-26393976 FAX:+886-4-26393125