

Твердотельные реле для печатных плат и интерфейсных модулей PI6W



RSR30...



RSR40...

Реле	Напряжение управления, V DC	Коммутирующая способность		Цена, у. е. с НДС	
		Ток нагрузки, А	Напряжение, V / род тока	розн.	опт
RSR30-D05-A1-24-020-1	3...10	2	240 / AC	7,39	7,02
RSR30-D12-A1-24-020-1	7...20			7,56	7,18
RSR30-D24-A1-24-020-1	18...32			7,64	7,26
RSR30-D05-D1-04-025-1	3...10	2,5	48 / DC	6,80	6,46
RSR30-D12-D1-04-025-1	7...20			6,97	6,62
RSR30-D24-D1-04-025-1	18...32			7,09	6,74
RSR30-D48-D1-04-025-1	38...58			7,26	6,89
RSR30-D05-D1-02-040-1	3...10	4	24 / DC	6,22	5,91
RSR30-D12-D1-02-040-1	7...20			6,37	6,05
RSR30-D24-D1-02-040-1	18...32			6,50	6,18
RSR30-D48-D1-02-040-1	38...58			6,50	6,18
RSR30-D05-D1-24-010-1	3...10	1	240 / DC	7,98	7,58
RSR30-D12-D1-24-010-1	7...20			7,98	7,58
RSR30-D24-D1-24-010-1	18...32			7,98	7,58
RSR30-D48-D1-24-010-1	38...58			7,98	7,58
RSR40-D05-A1-24-010-1-0	3...10	1	240 / AC	6,38	6,06
RSR40-D12-A1-24-010-1-0	7...20			6,38	6,06
RSR40-D24-A1-24-010-1-0	18...32			6,38	6,06
RSR40-D05-D1-02-040-0-P	3...10	4	24 / DC	5,88	5,59
RSR40-D12-D1-02-040-0-P	7...20			5,88	5,59
RSR40-D24-D1-02-040-0-P	18...32			5,88	5,59
RSR40-D05-D1-02-040-0-N	3...10			5,88	5,59
RSR40-D12-D1-02-040-0-N	7...20			5,88	5,59
RSR40-D24-D1-02-040-0-N	18...32			5,88	5,59